

Bird BLazer

World's first indoor laser bird repeller - Remote controlled Fat Beam technology safely frightens birds away

Laser beams are well-documented to chase away pest birds. The beam seeks out their roosting-spots, alarming and confusing them, causing them to flee. This technological breakthrough makes current hand-held, labor-intensive lasers obsolete, opening this proven method of bird control for general industrial use.

- 10 milliwatts of tri-colored fat-beam laser power (yellow, green, red)
- State-of-the-art, fully registered, consumer-safe device
- Works day and night: laser beams constantly change pattern and location to prevent acclimation
- **Model #: BLAZER**



Coverage: up to 10,000 feet
Pests: birds (pigeons, sparrows, starlings, swallows), bats, rodents and more
Uses: hangars, warehouses, plants, tunnels, loading docks, train sheds, boat houses, underpasses, storage sheds, sports arenas, convention centers, parking garages, car washes and other enclosed or semi-enclosed area

SPECIFICATIONS:
Laser Power: 10mW FAT BEAM
Unit Power: 50 watts
Laser Colors: Green, yellow, red
Net Weight: 9 lbs/4Kgs
Power: AC 100V~120V or 220V~240V, @ 50/60Hz
Electric Current: 110v = 0.45 amps 220v = 0.23 amps
Classification: 3R
Size: 9" x 11" x 6.75"
Fuse: 20mmx2A slow-blow
Housing: Metal
Beam Divergence: < 1.5 mrad
Operating Temperature: 64-77°F/18-25°C
Safe Temperature for Use: 41-104°F/5-40°C



NEW! Bird-X Laser - Indoor / Bird-X Laser - Outdoor

Laser Technology in convenient, economically-sized units for smaller areas. Now available for outdoor use also (stake or bracket mount) to deter roosting birds, geese on ponds, etc.

- REMOTE CONTROLLED for safety and convenience; includes optional timer function
- State-of-the-art, fully registered, consumer-safe devices
- RED and GREEN Laser beams constantly change to prevent acclimation



BIRD-X LASER INDOOR - SPECIFICATIONS:
Laser Power: Red: 650nm100mW, green :532nm50mW
Unit Power: 4.9mW RED+4.9mW GREEN
Laser Color: Red + green
Net Weight: 1.5kg
Power: AC100-240V,50-60Hz
Electric Current: 100mA
Classification: CLASS 3R
Size (mm): L(18.5)*W(14.8)*H(7.0) CM
Fuse: 2A
Housing: Cast aluminum
Beam Divergence: 60°
Operating Temperature: 0°C-40°C
Safe Temperature for Use: 0°C-35°C

BIRD-X LASER OUTDOOR - SPECIFICATIONS:
Laser Power: Red: 650nm100mW, green :532nm50mW
Unit Power: 1mW RED+1mW GREEN
Laser Color: Red + green
Net Weight: 1.5kg
Power: AC100-240V,50-60Hz
Electric Current: 100mA
Classification: CLASS 3R
Size (mm): L(16.5)*W(13.8)*H(13.8) CM
Fuse: 2A
Housing: Cast aluminum
Beam Divergence: 60°
Operating Temperature: -20°C-40°C
Safe Temperature for Use: -10°C-35°C



- Model #'s:**
- **BX-LASER-IN**
 - **BX-LASER-OUT**

